

# Gateway 26-inch LCD TV Specifications

Specifications are subject to change without notice or obligation.

---

## Display Panel

---

Screen size	Diagonal 26-inch
Aspect ratio	16:9 wide
Number of pixels	1280 (Horizontal, RGB Trio) × 768 (Vertical) pixels
Pixel pitch	0.4425 × 0.4425 mm
Luminance	450 cd/m <sup>2</sup> , at APL13% typical
Contrast ratio	600:1 typical
Response time	16 ms typical
Colors	16.7 M colors / 8 bits
Viewing angle	85° Horizontal / 85° Vertical

---

## Power Source

---

Input voltage	90 ~ 264 Vac, 47 Hz -63 Hz
Input current	1.7 A
Power consumption	150 Watts typical
Stand-by and Power Save	5 Watts max.

---

## Video Formats (A/V, S)

---

NTSC, PAL, SECAM

---

---

**Connector Types**

---

14	RCA jacks for audio, video, and YP <sub>B</sub> P <sub>R</sub>
2	6-pin Din S-terminal for S-Video
1	24-pin DVI/HDCP
1	15-pin D-SUB for RGB
1	F-terminal coax

---

---

**Video Signal, S-Video**

---

Type	Analog
Polarity	Positive
Amplitude	Y: 1 Vp-p, C: 0.286 Vp-p
Input impedance	75 ohms

---

---

**YP<sub>B</sub>P<sub>R</sub> Signal (Component)**

---

Type	Analog
Polarity	Positive
Amplitude	Y: 1 Vp-p, UV: 0.286 Vp-p
Input impedance	75 ohms

---

---

**RGB Signal**

---

Type	Analog
Polarity	Positive or Negative
Amplitude	RGB: 0.7 Vp-p

---

---

**Audio Signal**

---

Analog 500 mV rms /more than 22 Kohm

---

**Pin Assignments for D-SUB Connector (In/Loop Out)**

<b>Pin</b>	<b>Signal Assignment</b>	<b>Pin</b>	<b>Signal Assignment</b>	<b>Pin</b>	<b>Signal Assignment</b>
1	RED	6	RED GND	11	GND
2	GREEN	7	GREEN GND	12	SDA
3	BLUE	8	BLUE GND	13	H-SYNC
4	GND	9	+5 V for DDC	14	V-SYNC
5	GND	10	GND	15	SCL

**Pin Assignments for DVI-D Connector**

<b>Pin</b>	<b>Signal Assignment</b>	<b>Pin</b>	<b>Signal Assignment</b>
1	TMDS DATA 2 –	13	TMDS DATA 3 +
2	TMDS DATA 2 +	14	+ 5 V
3	TMDS DATA 2/4 SHIELD	15	GND
4	TMDS DATA 4 –	16	HOT PLUG DETECT
5	TMDS DATA 4 +	17	TMDS DATA 0 –
6	DDC CLOCK	18	TMDS DATA 0 +
7	DDC DATA	19	TMDS DATA 0/5 SHIELD
8	NC	20	TMDS DATA 5 –
9	TMDS DATA 1 –	21	TMDS DATA 5 +
10	TMDS DATA 1 +	22	TMDS CLOCK SHIELD
11	TMDS DATA 1/3 SHIELD	23	TMDS CLOCK –
12	TMDS DATA 3 –	24	TMDS CLOCK –

<b>RGB For VESA Standard</b>						
<b>Mode No.</b>	<b>Resolution</b>	<b>Refresh Rate (Hz)</b>	<b>Horizontal Frequency (KHz)</b>	<b>Vertical Frequency (Hz)</b>	<b>V-Sync Polarity (TTL)</b>	<b>H-Sync Polarity (TTL)</b>
1	720 × 400	70	31.47	70.0	+	-
2	640 × 480	60	31.47	60.0	-	-
3	640 × 480	72	37.86	72.0	-	-
4	640 × 480	75	37.50	75.0	-	-
5	640 × 480	85	43.4	85.0	-	-
6	800 × 600	56	35.16	56.0	+	-
7	800 × 600	60	37.88	60.0	+	+
8	800 × 600	72	48.08	72.0	+	+
9	800 × 600	75	46.88	75.0	+	+
10	800 × 600	85	53.70	85.0	+	+
11	1024 × 768	60	48.36	60.0	-	-
12	1024 × 768	70	56.48	70.0	-	-
13	1024 × 768	75	60.02	75.0	+	+
14	1024 × 768	85	68.70	85.0	+	+

<b>RGB For Apple Standard</b>						
<b>Mode No.</b>	<b>Resolution</b>	<b>Refresh Rate (Hz)</b>	<b>Horizontal Frequency (KHz)</b>	<b>Vertical Frequency (Hz)</b>	<b>V-Sync Polarity (TTL)</b>	<b>H-Sync Polarity (TTL)</b>
15	832 × 624	75	49.7	75.00	-	-
16	1024 × 768	75	60.2	75.00	-	-

<b>YP<sub>B</sub>P<sub>R</sub> for Component</b>		
<b>Mode</b>	<b>Resolution</b>	<b>Refresh Rate</b>
1	480i, 480p, 720p, 1080i	60

---

**Maximum Resolution**

---

Up to 1280 × 768

---

---

**Dimensions**                      **With/Stand**

---

Width                                      32.60 in. (828 mm)

---

Height                                     19.72 in. (501 mm)

---

Depth                                      8.47 in. (215 mm)

---

---

**Weight**

---

Net weight                                30.86 lbs (14.0 kgs)

---

---

**Operating**

---

Temperature                                0~35°C (32~95°F)

---

Relative humidity                         10~90%

---

Pressure                                    0~12,000 feet

---

---

**Non-Operating**

---

Temperature                                -20~60°C (-4~140°F)

---

Relative humidity                         10~90%

---

Pressure                                    0~40,000 feet

---

Vibration                                    1.0 G / 2~200 Hz (sweep), 60 min. per axis

---

---

**Sound**

---

2 Speakers

5 W

---

---

**Reliability Requirement**

---

The MTBF is 50,000 hours under operation at 25±5°C (Half luminosity, motion picture)

---

---

**Emissions Requirement**

---

Your LCD TV meets the EMI limits in all screen modes as qualified by FCC class B part 15.

---

Many products for Gateway and its subsidiaries are custom engineered by our suppliers to Gateway specifications and may vary from similarly marketed products.

MAN MON QTA 26" LCD TV SPEC R0 12/03



8509485